

L485 - 5 stations

- **Designed for optimum exercise biomechanics.** To guarantee smooth, natural movements for full muscle concentration.
- Calibrated weights. For guaranteed weight person.
- **Hard chrome guides and IGUS drylining bushing.** Offering a silent, sliding action and minimum maintenance. The bushings are resistant to friction and to high temperatures.
- High resistance 5 mm and 6 mm thick coated Steel cable, for smooth, secure performance.
- **360° free hold**, for a more natural exercise, adapted to the anatomical movement of the arms of each particular user, whilst maintaining control. Controlled mobility.
- **Magnetic weight plate selectors.** The magnets ensure that there is no possibility of the selector coming out during training.
- Stainless steel components. Designed to offer long-lasting durability.
- Use of laser cutting technology, for optimum tube cutting precision.
- **Structure of 4 mm thick ST-37/40 steel frame** and pulley support plates of 8 mm thick steel frame. Offers guaranteed durability.
- Multiple training positions at the ergoline.
- **Three layer coating.** The design of this professional, up-to-date, stylish system is enhanced still further by its -layer coating comprising an initial anti-corrosion primer, for guaranteed durability, followed by an epoxy powder layer and fin.
- Structure raised 50mm above floor level with rubber tipped feet. This provides access for cleaning and vacuuming without scratching the paint.
- Easy access to all elements of control and load selection from the working position of the user.
- Adjustable support in height.
- Positions in each tower: high pulley with seat, double ergoline with adjustable pulley, rowing with short pulley and high pulley without seat.
- Accessories: triceps rope, three short rope grips, two long rope grips and dorsal pull rod.
- According to the UNE-EN 957 regulation.
- Legs with rubber protections.

L485 5 stations

- **Injected core fireproof seat.** Unlike the classic foam padded particle boards, the injected core offers the advantage of uniformity, anti-distortion and greater anti-bacterial protection.
- An ergoline in the other side of the connectors.
- Support for chin ups.



Specifications

Length: 490 cm / 193"

Width (with folded arms): 170 cm / 67"

Width (with fully extended arms): 356 / 140"

Maximum Height (with arms in the highest position): 257 cm / 102"

Load in each pulley: 90kg